



# LubeCon Series 1/M 200 Lubricant

## Description

LubeCon Series I/M 200 Lubricant is a heavy-duty, anti-wear fluid designed specifically for use on conveyors, plant maintenance equipment or other devices with LubeCon automatic lubricators. This synergistic combination of lubrication equipment and premium lubricant provides positive and precise lubrication with maximum protection over a temperature range of -65°F to +600°F.

Lubecon Series I/M 200 Lubricant is designed to be a thin-film, dry-film lubricant that first acts as a penetrant and cleaner. The highly penetrating and creeping characteristics serve to dissolve solidified grease and accumulated carbon residue. A thin film of highly stable lubricating solids carried to the contact points offers superior film strength in addition to the fluid lubricant. Low initial viscosity allows for excellent penetration, solvency, and precise lubrication.

## Application

LubeCon I/M 200 Lubricant can be used on the following applications:

Valves	Cables, Wire Rope	Linkages	Hinges	Parts Assembly
Threads	Bearings	Chains (all types)	Slides	Control Mechanisms
Machinery Gears	Sprockets	Rollers	Firearms	Locking Mechanisms
Frozen Mechanisms	Press, Slide Fits			

## Typical Characteristics

	Test Method	Value
Kinematic Viscosity, cSt @ 40C	ASTM D 445	6
Pour Point, °C/°F	ASTM D 97	-65 / -54
Flash Point, °C/°F	ASTM D 93, PMCC	118 / 244
Rust Protection	ASTM D 665 A&B	Pass
Copper Corrosion, Rating	ASTM D 130	1B
Four Ball Wear, mm	ASTM D 4172	0.6
Falex Pin & Vee, # teeth	ASTM D 2670	5
Color	Visual	Dark Gray
Solids Lubricant	-	Molybdenum Sulfide (Suspension Grade)

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by LUBECON USA, LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

LUBECON USA, LLC 201 N Webster St. White Cloud, MI 49349  
1-800-582-3266

[www.lubeconusa.com](http://www.lubeconusa.com)