



## LubeCon Series I Lubricant

### Description

LubeCon Series I fluids are heavy-duty, anti-wear lubricants designed specifically for use on conveyors, plant maintenance equipment or other devices with LubeCon automatic lubricators. This synergistic combination of lubrication equipment and premium lubricant provides positive and precise lubrication with maximum protection over a temperature range of -65°F to +400°F.

LubeCon Series I fluid is designed to be thin-film/dry-film lubricant that first acts as a penetrant and cleaner. The highly penetrating and creeping characteristics serve to dissolve solidified grease and accumulated carbon residue. A thin film of highly stable Lubricating Solids carried to the contact points offers superior film strength in addition to the fluid lubricant. LubeCon Series I is engineered for optimized application by LubeCon equipment allowing for precise amounts of the fluid to be directed to the lube points at the right time, every time.

### Application

- Cables, Wire Rope
- Linkages
- Threads
- Bearings
- Chains (all types)
- Slides
- Sprockets
- Rollers
- Machinery Gears
- Press, Slide Fits
- Locking Mechanisms
- Frozen Mechanisms
- Parts Assembly
- Control Mechanisms
- Hinges
- Firearms
- Valves

### Typical Characteristics

	Unit	Test Method	Value
Kinematic Viscosity	@ 40 °c	ASTM D-445 cSt	5.5
Viscosity Index	-	ASTM D-2270	135
Pour Point	°F/°C	ASTM D-97	-65/-54
Flash Point	°F/°C	ASTM D-56	61/142
Rust protection	Parts A & B	ASTM D-665	Pass
Copper Corrosion	-	ASTM D-130	1b
Four Ball Wear	-	ASTM D-4172, mm	0.6
Falex Pin and Vee Wear	Teeth	ASTM-D 2670	5
Color	-	Visual	Dark Grey
Solids Lubricant	-	-	Molybdenum Disulfide (Suspension Grade)

LubeCon logo are trademarks of LubeCon USA LLC, used under license

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

LubeCon USA LLC 201 N. Webster Rd. White Cloud, MI 49349  
customer.care@lubeconusa.com  
(800) 582-3266  
**www.lubeconusa.com**  
LubeCon Series I Lubricant